

MODULAR DC BACKUP AC/DC

series SBN DC - AC/DC

NOMINAL VOLTAGE

24 Vdc, 48 Vdc, 110 Vdc, 125 Vdc, 220 Vdc

Modular DC Backup AC/DC designed for DC appliance. Power for backup covered from internal batteries, maintenance and charged with rectifier's modules. Power source design ensures high reliability, operation safety, enable fast and easy service for various applications.



ALBAT'S Modular DC Backup AC/DC system with its Modular design represents a perfect solution for a wide range application in the:

- Telecommunication,
- Industrial and
- Energetics market.

MAIN FEATURES:

- Switched-mode rectifier
- Power range per module from 400 W to 4400 W
- Input voltage from 90 V to 320 Vac
- Suitable for all common voltages: 12V, 24V, 48V, 108 to 110V, 125Vdc, 216 to 220 Vdc
- 19" Rack design
- Modular design
- Digital controller
- Internal battery

AVAILABILITY:

- N+1 redundancy
- Hot swap conception
- Energy save via sleep mode
- Temperature controlled charging
- Battery test during operation
- Local and remote control
- LVDB system protection battery
- Over voltage protection for system and modules
- Enable the additional power extension

ECONOMIC EFFICIENCY:

- High performance beside low volume and weight
- High efficiency, power factor 0,99
- Suitable for lead and NiCad batteries
- All-inclusive system

ALBAT provide completely Design by your technical request, Production, Assembly and Service in warranty and after-warranty period.

The production process is in accordance with the standards ISO 9001:2008 and ISO 14001:2004. All products are in compliance with IEC and EN standards.

MODULAR DC BACKUP AC/DC



Technical Specification

OUTPUT																	
Nominal Voltage Vdc	24				48						110		125		220		
Operation Voltage Vdc	20	21	43	42	42	42	44	44	42	90	90	180	90	180	180	320	
	to	To	to	to	to	to	to	to	to	to	to	to	to	to	to	to	
Power per Module kW	0,4	3,1	0,3	0,65	1,0	1,2	2,0	2,4	4,0	1,1	4,4	1,1	4,4	1,1	4,4		
Power per Shelf kW	2,0	15,5	0,9	3,25	5,0	6,0	8,0	9,6	20,0	6,6	22	6,6	22	6,6	22		
Max Power per System kW	Per technical request / Parallel function of Modules / Shelves																
Height per Shelf U	2	4	1	2	4	1	2	1	4	4	4	4	4	4	4		
Load regulation %	Static $\leq \pm 0,5$																
Line regulation %	Static $\leq \pm 0,1$																
INPUT																	
Nominal Voltage Vac	100 / 110 / 115 / 120 / 127 / 208 / 220 / 230 / 240																
Operating Voltage Vac	90	176	90	90	150	90	187	187	187	176							
	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to		
Extended Voltage Vac (de-rated)	-	176	-	90	150	277	187	90	187	176							
		to		to	to	to	to	to	to	to	to	to	to	to	to		
Frequency Hz	45	47	45	45	45	45	45	45	66	45							
	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to		
Power Factor	$> 0,99$																
THD %	≤ 5																
Efficiency %	> 90	> 90	$> 93,8$	> 91	> 91	> 93	$> 94,2$	> 96	$> 94,9$	> 93	> 92	> 93	> 92	> 93	> 92		
PERFORMANCE / FEATURES																	
Indicators	AC main OK; Module OK; Module fail;																
Adjustments, via controller	Float voltage; Equalize voltage; High & low voltage alarms; High voltage shutdown; Current limit; Slope; Start delay;																
Protection	Current limit / short circuit; Start delay; Input / output fuses; Output high voltage shutdown; Power limiting; Thermal foldback / shutdown; Input transient; AC low line foldback shutdown;																
ENVIRONMENTAL																	
Standard temperature °C	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40 to +55				-40 to +55			
	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to		
Extended temperature °C	-40 to +85 (de-rated)							-40 to +75 (de-rated)									
Humidity %	0 to 95 RH non-condensing																
Elevation m (de-rated more than 2000)	-500	-500	-500	-500	-500	-500	-60	-500	-500	-500							
	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to		
	3000	4000	3000	3000	4000	3000	4000	3000	4000	2800							
CONTROLLER																	
Features	High resolution color touchscreen LCD display for local access; Embedded web based UI accessed via Ethernet using internet browser; Built in multi-tone speaker; LED indicators (green, amber, red);																
Battery	Automatic battery test; Battery runtime and capacity indication; Charge current Control; Temperature compensation; Equalize; Apsorption charge settings with entry/exit criteria;																
System	User management – Admin + 5 users with configurable access rights; Advanced inventory management with custom inventory items; User configurable alarms and custom data; Advanced equation editing with timers and counters; Software, firmware, and configuration file upgrade management; CAN Bus interface to power electronics and peripherals; Custom data logging and performance monitoring; Power save feature for optimizing system efficiency;																
Communication ports	2 x Ports for communication with shelves; 2 x Ethernet ports front and rear; 2 x USB ports front and rear;																
Inputs (possibility of extension)	4 x Voltage; 4 x Shunt; 4 x Temp; 8 x Digital; 12 x Relay;									2 x Voltage; 1 x Shunt; 2 x Temp; 4 x Digital; 6 x Relay;							
MECHANICAL																	
Cabinet dimension	600 x 600 x 2000 mm + 100 mm / or different per technical request																
Cabinet protection	IP 21 or IP 54 or IP 65 (standard or AIR-conditioned or Seismic resistance) / or different per technical request																
Installation	Indoor / Outdoor																
AGENCY COMPLIANCE																	
Safety	CSA C22.2 NO 60950-1-03; CE MARKED; UL 60950-1 1th edition; IEC/EN 60950-1;																
EMC / Emission	CFR47 PART 15 CLASS A; ICES-03 CLASS A; EN 55022 CLASS A; C-TICK; EN 61000-3-2; EN 61000-3-3;																
EMC / Immunity	EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; ANSI/IEEE C62.41 CAT B3																

MODULAR DC BACKUP AC/DC

FUNCTIONAL DIAGRAM

